

# SAP WorkSheet: Existing dwelling (SAP)

User Details:

**Assessor Name:**

**Software Name:** Stroma FSAP 2009

**Stroma Number:**

**Software Version:**

Version: 1.4.0.55

Property Address: Traditional Semi

**Address :**

432, Saffron Lane, LEICESTER, LE2 6SB

1. Overall dwelling dimensions:

	Area(m <sup>2</sup> )	Ave Height(m)	Volume(m <sup>3</sup> )
Ground floor	40.5 (1a) x	2.5 (2a) =	101.25 (3a)
First floor	40.5 (1b) x	2.5 (2b) =	101.25 (3b)
Total floor area TFA = (1a)+(1b)+(1c)+(1d)+(1e)+.....(1n)	81 (4)		
Dwelling volume		(3a)+(3b)+(3c)+(3d)+(3e)+.....(3n) =	202.5 (5)

2. Ventilation rate:

	main heating	Secondary heating	other	total	m <sup>3</sup> per hour
Number of chimneys	1	+ 0	+ 0	= 1	x 40 = 40 (6a)
Number of open flues	0	+ 0	+ 0	= 0	x 20 = 0 (6b)
Number of intermittent fans				0	x 10 = 0 (7a)
Number of passive vents				2	x 10 = 20 (7b)
Number of flueless gas fires				2	x 40 = 80 (7c)

Infiltration due to chimneys, flues and fans = (6a)+(6b)+(7a)+(7b)+(7c) =

If a pressurisation test has been carried out or is intended, proceed to (17), otherwise continue from (9) to (16)

Number of storeys in the dwelling (ns)

Additional infiltration

Structural infiltration: 0.25 for steel or timber frame or 0.35 for masonry construction

if both types of wall are present, use the value corresponding to the greater wall area (after deducting areas of openings); if equal user 0.35

If suspended wooden floor, enter 0.2 (unsealed) or 0.1 (sealed), else enter 0

If no draught lobby, enter 0.05, else enter 0

Percentage of windows and doors draught stripped

Window infiltration  $0.25 - [0.2 \times (14) \div 100] =$

Infiltration rate  $(8) + (10) + (11) + (12) + (13) + (15) =$

Air permeability value, q50, expressed in cubic metres per hour per square metre of envelope area

If based on air permeability value, then (18) = [(17) ÷ 20]+(8), otherwise (18) = (16)

Air permeability value applies if a pressurisation test has been done or a degree air permeability is being used

Number of sides on which sheltered

Shelter factor  $(20) = 1 - [0.075 \times (19)] =$

Infiltration rate incorporating shelter factor  $(21) = (18) \times (20) =$

Infiltration rate modified for monthly wind speed

Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

Monthly average wind speed from Table 7

(22)m= 5.4	5.1	5.1	4.5	4.1	3.9	3.7	3.7	4.2	4.5	4.8	5.1
------------	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

# SAP WorkSheet: Existing dwelling (SAP)

Wind Factor (22a)m = (22)m ÷ 4

(22a)m=	1.35	1.27	1.27	1.12	1.02	0.98	0.92	0.92	1.05	1.12	1.2	1.27
---------	------	------	------	------	------	------	------	------	------	------	-----	------

Adjusted infiltration rate (allowing for shelter and wind speed) = (21a) x (22a)m

1.95	1.84	1.84	1.62	1.48	1.41	1.33	1.33	1.51	1.62	1.73	1.84
------	------	------	------	------	------	------	------	------	------	------	------

Calculate effective air change rate for the applicable case

If mechanical ventilation:

0	(23a)
0	(23b)
0	(23c)

If exhaust air heat pump using Appendix N, (23b) = (23a) x Fmv (equation (N5)) , otherwise (23b) = (23a)

If balanced with heat recovery: efficiency in % allowing for in-use factor (from Table 4h) =

a) If balanced mechanical ventilation with heat recovery (MVHR) (24a)m = (22b)m + (23b) x [1 - (23c) ÷ 100]

(24a)m=	0	0	0	0	0	0	0	0	0	0	0	0
---------	---	---	---	---	---	---	---	---	---	---	---	---

b) If balanced mechanical ventilation without heat recovery (MV) (24b)m = (22b)m + (23b)

(24b)m=	0	0	0	0	0	0	0	0	0	0	0	0
---------	---	---	---	---	---	---	---	---	---	---	---	---

c) If whole house extract ventilation or positive input ventilation from outside

if (22b)m < 0.5 x (23b), then (24c) = (23b); otherwise (24c) = (22b)m + 0.5 x (23b)

(24c)m=	0	0	0	0	0	0	0	0	0	0	0	0
---------	---	---	---	---	---	---	---	---	---	---	---	---

d) If natural ventilation or whole house positive input ventilation from loft

if (22b)m = 1, then (24d)m = (22b)m otherwise (24d)m = 0.5 + [(22b)m² x 0.5]

(24d)m=	1.95	1.84	1.84	1.62	1.48	1.41	1.33	1.33	1.51	1.62	1.73	1.84
---------	------	------	------	------	------	------	------	------	------	------	------	------

Effective air change rate - enter (24a) or (24b) or (24c) or (24d) in box (25)

(25)m=	1.95	1.84	1.84	1.62	1.48	1.41	1.33	1.33	1.51	1.62	1.73	1.84
--------	------	------	------	------	------	------	------	------	------	------	------	------

### 3. Heat losses and heat loss parameter:

ELEMENT	Gross area (m <sup>2</sup> )	Openings m <sup>2</sup>	Net Area A ,m <sup>2</sup>	U-value W/m <sup>2</sup> K	A X U (W/K)	k-value kJ/m <sup>2</sup> ·K	A X k kJ/K
Doors			1.2	x 1.26	= 1.512		
Windows			0.6	x 1/[1/( 1.8 )+ 0.04]	= 1.01		
Floor			40.5	x 0.58	= 23.49		
Walls	47	7.2	39.8	x 1.6	= 63.68		
Roof	40.5	0	40.5	x 0.16	= 6.48		
Total area of elements, m <sup>2</sup>			128				

\* for windows and roof windows, use effective window U-value calculated using formula  $1/[1/(1/U\text{-value})+0.04]$  as given in paragraph 3.2

\*\* include the areas on both sides of internal walls and partitions

Fabric heat loss, W/K = S (A x U) (26)...(30) + (32) = 105.24 (33)

Heat capacity Cm = S(A x k ) ((28)...(30) + (32) + (32a)...(32e) = 8736.5 (34)

Thermal mass parameter (TMP = Cm ÷ TFA) in kJ/m<sup>2</sup>K Indicative Value: Low 100 (35)

For design assessments where the details of the construction are not known precisely the indicative values of TMP in Table 1f can be used instead of a detailed calculation.

Thermal bridges : S (L x Y) calculated using Appendix K 19.2 (36)

if details of thermal bridging are not known (36) = 0.15 x (31)

Total fabric heat loss (33) + (36) = 124.44 (37)

Ventilation heat loss calculated monthly (38)m = 0.33 x (25)m x (5)

Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	
(38)m=	130.03	122.81	122.81	108.36	98.73	93.91	89.09	89.09	101.13	108.36	115.58	122.81

Heat transfer coefficient, W/K (39)m = (37) + (38)m 233 (39)

(39)m=	254.47	247.24	247.24	232.8	223.16	218.35	213.53	213.53	225.57	232.8	240.02	247.24
--------	--------	--------	--------	-------	--------	--------	--------	--------	--------	-------	--------	--------

Average = Sum(39)<sub>1...12</sub> /12= 233 (39)

# SAP WorkSheet: Existing dwelling (SAP)

Heat loss parameter (HLP), W/m<sup>2</sup>K

$$(40)m = (39)m \div (4)$$

(40)m=	3.14	3.05	3.05	2.87	2.76	2.7	2.64	2.64	2.78	2.87	2.96	3.05	Average = Sum(40) <sub>1...12</sub> / 12 =	2.88	(40)
--------	------	------	------	------	------	-----	------	------	------	------	------	------	--	------	------

Number of days in month (Table 1a)

Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	(41)m=	31	28	31	30	31	30	31	30	31	30	31	(41)
-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	--------	----	----	----	----	----	----	----	----	----	----	----	------

## 4. Water heating energy requirement:

kWh/year:

Assumed occupancy, N

2.48

(42)

$$\text{if TFA} > 13.9, N = 1 + 1.76 \times [1 - \exp(-0.000349 \times (\text{TFA} - 13.9)2)] + 0.0013 \times (\text{TFA} - 13.9)$$

$$\text{if TFA} \leq 13.9, N = 1$$

Annual average hot water usage in litres per day Vd,average = (25 x N) + 36

98.04

(43)

Reduce the annual average hot water usage by 5% if the dwelling is designed to achieve a water use target of not more than 125 litres per person per day (all water use, hot and cold)

Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

Hot water usage in litres per day for each month Vd,m = factor from Table 1c x (43)

(44)m=	107.84	103.92	100	96.08	92.16	88.24	88.24	92.16	96.08	100	103.92	107.84	Total = Sum(44) <sub>1...12</sub> =	1176.47	(44)
--------	--------	--------	-----	-------	-------	-------	-------	-------	-------	-----	--------	--------	-------------------------------------	---------	------

Energy content of hot water used - calculated monthly = 4.190 x Vd,m x nm x DTm / 3600 kWh/month (see Tables 1b, 1c, 1d)

(45)m=	160.31	140.21	144.68	126.14	121.03	104.44	96.78	111.06	112.38	130.97	142.97	155.25	Total = Sum(45) <sub>1...12</sub> =	1546.23	(45)
--------	--------	--------	--------	--------	--------	--------	-------	--------	--------	--------	--------	--------	-------------------------------------	---------	------

If instantaneous water heating at point of use (no hot water storage), enter 0 in boxes (46) to (61)

(46)m=	24.05	21.03	21.7	18.92	18.15	15.67	14.52	16.66	16.86	19.65	21.44	23.29	(46)
--------	-------	-------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	------

Water storage loss:

a) If manufacturer's declared loss factor is known (kWh/day):

0

(47)

Temperature factor from Table 2b

0

(48)

Energy lost from water storage, kWh/year

$$(47) \times (48) =$$

(49)

If manufacturer's declared cylinder loss factor is not known:

Cylinder volume (litres) including any solar storage within same

0

(50)

If community heating and no tank in dwelling, enter 110 litres in box (50)

Otherwise if no stored hot water (this includes instantaneous combi boilers) enter '0' in box (50)

Hot water storage loss factor from Table 2 (kWh/litre/day)

0

(51)

Volume factor from Table 2a

0

(52)

Temperature factor from Table 2b

0

(53)

Energy lost from water storage, kWh/year

$$((50) \times (51) \times (52) \times (53)) =$$

(54)

Enter (49) or (54) in (55)

0

(55)

Water storage loss calculated for each month

$$((56)m = (55) \times (41)m)$$

(56)m=	0	0	0	0	0	0	0	0	0	0	0	0	(56)
--------	---	---	---	---	---	---	---	---	---	---	---	---	------

If cylinder contains dedicated solar storage, (57)m = (56)m x [(50) - (H11)] ÷ (50), else (57)m = (56)m where (H11) is from Appendix H

(57)m=	0	0	0	0	0	0	0	0	0	0	0	0	(57)
--------	---	---	---	---	---	---	---	---	---	---	---	---	------

Primary circuit loss (annual) from Table 3

0

(58)

Primary circuit loss calculated for each month (59)m = (58) ÷ 365 × (41)m

(59)m=	0	0	0	0	0	0	0	0	0	0	0	0	(59)
--------	---	---	---	---	---	---	---	---	---	---	---	---	------

Combi loss calculated for each month (61)m = (60) ÷ 365 × (41)m

(61)m=	20.43	18.45	20.42	19.75	20.4	19.73	20.37	20.39	19.74	20.41	19.77	20.43	(61)
--------	-------	-------	-------	-------	------	-------	-------	-------	-------	-------	-------	-------	------

# SAP WorkSheet: Existing dwelling (SAP)

Total heat required for water heating calculated for each month (62)m =  $0.85 \times (45)m + (46)m + (57)m + (59)m + (61)m$

(62)m=	180.75	158.66	165.11	145.89	141.43	124.17	117.16	131.45	132.12	151.38	162.73	175.68		(62)
--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--	------

Solar DHW input calculated using Appendix G or Appendix H (negative quantity) (enter '0' if no solar contribution to water heating)

(add additional lines if FGHRS and/or WWHRS applies, see Appendix G)

(63)m=	0	0	0	0	0	0	0	0	0	0	0	0		(63)
--------	---	---	---	---	---	---	---	---	---	---	---	---	--	------

Output from water heater

(64)m=	180.75	158.66	165.11	145.89	141.43	124.17	117.16	131.45	132.12	151.38	162.73	175.68		
	Output from water heater (annual) 1...12												1786.52	(64)

Heat gains from water heating, kWh/month  $0.25 \times [0.85 \times (45)m + (61)m] + 0.8 \times [(46)m + (57)m + (59)m]$

(65)m=	58.41	51.23	53.21	46.88	45.34	39.66	37.27	42.02	42.3	48.65	52.48	56.73		(65)
--------	-------	-------	-------	-------	-------	-------	-------	-------	------	-------	-------	-------	--	------

include (57)m in calculation of (65)m only if cylinder is in the dwelling or hot water is from community heating

## 5. Internal gains (see Table 5 and 5a):

Metabolic gains (Table 5), Watts

Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec		
(66)m=	148.89	148.89	148.89	148.89	148.89	148.89	148.89	148.89	148.89	148.89	148.89		(66)

Lighting gains (calculated in Appendix L, equation L9 or L9a), also see Table 5

(67)m=	96.69	85.88	69.84	52.88	39.53	33.37	36.06	46.87	62.91	79.87	93.23	99.38		(67)
--------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	--	------

Appliances gains (calculated in Appendix L, equation L13 or L13a), also see Table 5

(68)m=	330.62	334.05	325.41	307	283.77	261.93	247.35	243.91	252.56	270.97	294.2	316.04		(68)
--------	--------	--------	--------	-----	--------	--------	--------	--------	--------	--------	-------	--------	--	------

Cooking gains (calculated in Appendix L, equation L15 or L15a), also see Table 5

(69)m=	52.37	52.37	52.37	52.37	52.37	52.37	52.37	52.37	52.37	52.37	52.37	52.37		(69)
--------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	--	------

Pumps and fans gains (Table 5a)

(70)m=	10	10	10	10	10	10	10	10	10	10	10	10		(70)
--------	----	----	----	----	----	----	----	----	----	----	----	----	--	------

Losses e.g. evaporation (negative values) (Table 5)

(71)m=	-99.26	-99.26	-99.26	-99.26	-99.26	-99.26	-99.26	-99.26	-99.26	-99.26	-99.26	-99.26		(71)
--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--	------

Water heating gains (Table 5)

(72)m=	78.51	76.24	71.52	65.11	60.94	55.08	50.1	56.48	58.75	65.39	72.89	76.25		(72)
--------	-------	-------	-------	-------	-------	-------	------	-------	-------	-------	-------	-------	--	------

**Total internal gains =**  $(66)m + (67)m + (68)m + (69)m + (70)m + (71)m + (72)m$

(73)m=	617.83	608.18	578.78	536.99	496.24	462.39	445.5	459.27	486.22	528.23	572.31	603.67		(73)
--------	--------	--------	--------	--------	--------	--------	-------	--------	--------	--------	--------	--------	--	------

## 6. Solar gains:

Solar gains are calculated using solar flux from Table 6a and associated equations to convert to the applicable orientation.

Orientation:	Access Factor Table 6d	Area m <sup>2</sup>	Flux Table 6a	g_ Table 6b	FF Table 6c	Gains (W)					
East/West 0.9x	0.77	x	0.6	x	0.76	x	0.7	=	43.96		(76)
East/West 0.9x	0.77	x	0.6	x	0.76	x	0.7	=	85.21		(76)
East/West 0.9x	0.77	x	0.6	x	0.76	x	0.7	=	136.19		(76)
East/West 0.9x	0.77	x	0.6	x	0.76	x	0.7	=	202.2		(76)
East/West 0.9x	0.77	x	0.6	x	0.76	x	0.7	=	246.02		(76)
East/West 0.9x	0.77	x	0.6	x	0.76	x	0.7	=	256.71		(76)
East/West 0.9x	0.77	x	0.6	x	0.76	x	0.7	=	249.17		(76)
East/West 0.9x	0.77	x	0.6	x	0.76	x	0.7	=	216.86		(76)



# SAP WorkSheet: Existing dwelling (SAP)

## 9a. Energy requirements – Individual heating systems including micro-CHP)

### Space heating:

Fraction of space heat from secondary/supplementary system

0 (201)

Fraction of space heat from main system(s)

$(202) = 1 - (201) =$

1 (202)

Fraction of total heating from main system 1

$(204) = (202) \times [1 - (203)] =$

1 (204)

Efficiency of main space heating system 1

90.7 (206)

Efficiency of secondary/supplementary heating system, %

0 (208)

Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	kWh/year
-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	----------

Space heating requirement (calculated above)

1817.19	1524.98	1458.95	1100.76	756.2	0	0	0	0	936.37	1377.13	1722.62
---------	---------	---------	---------	-------	---	---	---	---	--------	---------	---------

$$(211)m = \{[(98)m \times (204)] + (210)m\} \times 100 \div (206) \quad (211)$$

2003.52	1681.35	1608.54	1213.63	833.73	0	0	0	0	1032.38	1518.34	1899.25
---------	---------	---------	---------	--------	---	---	---	---	---------	---------	---------

$$\text{Total (kWh/year)} = \text{Sum}(211)_{1...5,10...12} = \quad 11790.74 \quad (211)$$

Space heating fuel (secondary), kWh/month

$$= \{[(98)m \times (201)] + (214)m\} \times 100 \div (208)$$

0	0	0	0	0	0	0	0	0	0	0	0	0
---	---	---	---	---	---	---	---	---	---	---	---	---

$$\text{Total (kWh/year)} = \text{Sum}(215)_{1...5,10...12} = \quad 0 \quad (215)$$

### Water heating

Output from water heater (calculated above)

180.75	158.66	165.11	145.89	141.43	124.17	117.16	131.45	132.12	151.38	162.73	175.68
--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

Efficiency of water heater

87 (216)

90.35	90.34	90.31	90.25	90.1	87	87	87	87	90.17	90.29	90.34
-------	-------	-------	-------	------	----	----	----	----	-------	-------	-------

Fuel for water heating, kWh/month

$$(219)m = (64)m \times 100 \div (217)m$$

200.04	175.63	182.82	161.65	156.97	142.72	134.66	151.09	151.86	167.89	180.22	194.46
--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------	--------

$$\text{Total} = \text{Sum}(219a)_{1...12} = \quad 2000.03 \quad (219)$$

### Annual totals

Space heating fuel used, main system 1

kWh/year

11790.74

Water heating fuel used

kWh/year

2000.03

Electricity for pumps, fans and electric keep-hot

central heating pump: 130 (230c)

boiler with a fan-assisted flue 45 (230e)

Total electricity for the above, kWh/year sum of (230a)...(230g) = 175 (231)

Electricity for lighting

kWh/year

683.06 (232)

## 10a. Fuel costs - individual heating systems:

	Fuel kWh/year	Fuel Price (Table 12)	Fuel Cost £/year
Space heating - main system 1	(211) x	3.1	x 0.01 = 365.51 (240)
Space heating - main system 2	(213) x	0	x 0.01 = 0 (241)
Space heating - secondary	(215) x	0	x 0.01 = 0 (242)
Water heating cost (other fuel)	(219)	3.1	x 0.01 = 62 (247)

# SAP WorkSheet: Existing dwelling (SAP)

Pumps, fans and electric keep-hot (231) 11.46 x 0.01 = 20.06 (249)

(if off-peak tariff, list each of (230a) to (230g) separately as applicable and apply fuel price according to Table 12a  
Energy for lighting (232) 11.46 x 0.01 = 78.28 (250)

Additional standing charges (Table 12) 106 (251)

Appendix Q items: repeat lines (253) and (254) as needed

**Total energy cost** (245)...(247) + (250)...(254) = 631.85 (255)

## 11a. SAP rating - individual heating systems

Energy cost deflator (Table 12) 0.47 (256)

Energy cost factor (ECF)  $[(255) \times (256)] \div [(4) + 45.0] = 2.36$  (257)

**SAP rating (Section 12)** 67.12 (258)

## 12a. CO<sub>2</sub> emissions – Individual heating systems including micro-CHP

	Energy kWh/year	Emission factor kg CO <sub>2</sub> /kWh	Emissions kg CO <sub>2</sub> /year
Space heating (main system 1) (211) x	0.198	=	2334.57 (261)
Space heating (secondary) (215) x	0	=	0 (263)
Water heating (219) x	0.198	=	396.01 (264)
Space and water heating (261) + (262) + (263) + (264) =			2730.57 (265)
Electricity for pumps, fans and electric keep-hot (231) x	0.517	=	90.48 (267)
Electricity for lighting (232) x	0.517	=	353.14 (268)
Total CO <sub>2</sub> , kg/year	sum of (265)...(271) =		3174.19 (272)
<b>CO<sub>2</sub> emissions per m<sup>2</sup></b>	(272) ÷ (4) =		39.19 (273)
El rating (section 14)			66 (274)

## 13a. Primary Energy

	Energy kWh/year	Primary factor	P. Energy kWh/year
Space heating (main system 1) (211) x	1.02	=	12026.55 (261)
Space heating (secondary) (215) x	0	=	0 (263)
Energy for water heating (219) x	1.02	=	2040.03 (264)
Space and water heating (261) + (262) + (263) + (264) =			14066.58 (265)
Electricity for pumps, fans and electric keep-hot (231) x	2.92	=	511 (267)
Electricity for lighting (232) x	0	=	1994.54 (268)
'Total Primary Energy	sum of (265)...(271) =		16572.13 (272)
<b>Primary energy kWh/m<sup>2</sup>/year</b>	(272) ÷ (4) =		204.59 (273)